


# BES Series



MODEL  
**BES - 22L**

European high quality  
Class-B  
I-PREVACCUUM AUTOCLAVE  
built in vacuum pump  
Exposure temperature at least 110 & 134°C  
Chamber is in stainless steel made  
Printer is optional



Automatic record of the time of sterilization beginning & end  
The new-type control system will record the time of beginning & end of sterilization automatically

Fuzzy control of the boiler heating and preservation  
Adopting the technology of fuzzy control, it is much precise, and the temperature positive and negative deviation can be controlled within 1°C

Adjustable date&time mode  
The date & time mode can be adjusted on your will, ranging of 100 years

**European Class B standard**

It adopts B-class(EN-13060), with 3 times pre-vacuum preceding vacuum drying. Residual humidity is <math>\le 0.2</math>, vacuum measurement reaches -0.70 bar. It sterilizes and sanitizes miscellaneous packed or unpacked medical instrument, whether solid or A-type hollow, whether with multi-aperture or inset piper. It efficiently rid air from every hollow area of any hollow instrument, such as hand-piece, making sure that water steam reaches every corner. It is installed with BOWIC&DICK which measures the penetration of water steam.

With a LCD display, Chinese and English menu are available. A special curve can display all the sterilization process.

Mode	Current	power	Capacity	chamber size	pack size	Weight
	V/Hz	W	L	mm	mm	kg
DU-22	220/50	2300	22	Ø 250X450	700X610X530	59KG(Net: 50KG)

YOUJOY Ningbo Youjoy dental equipment Co.,Ltd - Address: Ningpo city north of the Changjiang River main road Hong Tangyu - 315033 - Phone: 0574-87564380 - Fax: 0574-87564010 - E-mail: sales@youjoy.cn - http://www.youjoy.cn

MODEL  
**BES-22L**

1 Top-designed reservoir, convenient for watering, cleaning. ( Please consult to table top autoclave standard EN13060):  
A.You can easily open the top cover for cleaning. With the top reservoir, over-heat of the autoclave is avoided.  
B.The reservoir is enlarged by 3.5 times of the original size, making it available for 20 cycles use.

2 With the function of automatic clean: After every 100 times of cycles, the autoclave will clean the pipe, steam generator and other parts automatically.

3 With the both testing function:  
A B&D testing function  
B LEAK testing function



7 Broad ventilation window design, convenience & fast of heat radiation.

6 LCD display gives the whole process of sterilization by means of curve and words.

4 the printer is optional to record every cycle during the sterilization.

5 Door-lock-design of the draining outlet and power switch acts perfect detail.

